Abstract Notification dated 28th November 1936.

The attention of the public is invited to the Notification relating to the auction sale of timber in the Saw Mill and Timber Depots at Shimoga on the 4th and 5th January 1937, respectively, published on pages 1985-1986, Part VI of the *Mysore Gazette* dated 10th December 1936.

Abstract Notification dated 29th November 1936.

The attention of the public is invited to the detailed Notification relating to the sale of Bamboos in the Shimoga Division at the District Forest Office at 2 P.M. on the 7th January 1937 published on pages 1987-1988, Part VI of the *Mysore Gazette* dated 10th December 1936.

P. KRISHNASWAMI RAO,
District Forest Officer.

KADUR FOREST DIVISION.

Abstract Notification dated the 1st December 1936.

The attention of the public is invited to the detailed notification regarding the sale of timber lying in the plantations of Koppa Range published on pages 1988-1990, Part VI of the *Mysore Gazette* dated 10th December 1936.

M. A. MUTHANNA,
District Forest Officer.

CHITALDRUG DISTRICT.

Abstract Notification dated the 30th November 1936.

It is hereby notified for general information that the exclusive right of collecting and removing Tangadi and Kakke barks on all Government unoccupied lands and State forests, from the date of confirmation to 30th June 1937 in the Challakere Unit, will be resold in public auction at the District Forest Office, Chitaldrug, at 2 P.M., on the 22nd December 1936, by the Deputy Commissioner, Chitaldrug District, or by an Assistant Commissioner of senior rank deputed by him, at the risk of the original lessee who has failed to pay the amount of the "Khist" which fell due on the 15th October 1936 on this account. For further particulars, please see detailed Notification No. E. 272-1077, dated the 8th April 1935, issued by the Chief Conservator of Forests in Mysore.

D. NARASIMHAMURTHY RAO,
District Forest Officer.

ENGINEERING DEPARTMENT

BUILDINGS DIVISION, BANGALORE.

Notification dated 7th December 1936.

Notice is hereby given that sealed tenders will be received at the Office of the Executive Engineer, Buildings Division, up to 4 P.M. on 2nd January 1937 for constructing a Gopuram over Sree Dharmarayaswamy Temple, Ulsoorpet, Bangalore City. An approximate estimate of quantities is given below. These quantities are not guaranteed. The work should be completed by the end of April 1937.

2. The plans, detailed estimate and conditions may be seen at the Executive Engineer's Office at Buildings Division, between the hours of 11 A.M. and 5 P.M.

3. Tenders should be submitted on printed forms which may be obtained from the Executive Engineer. The tenders should be accompanied by a statement in the form given below, showing the rates at which the different items specified will be executed.—

4. Each tender must be accompanied by a deposit of Rupees two hundred only in cash or Government Promissory Notes, as earnest money, and be superscribed "Tender for constructing a Gopuram over Sree Dharmarayaswamy Temple, Ulsoorpet, Bangalore City," in default of which, tenders will be rejected.

5. The final acceptance of any tender will rest with the Executive Engineer, who does not bind himself to accept the lowest or any tender or to assign any reason whatever for the rejection of any tender.

6. Within eight days of the acceptance of the tender, the successful competitor will be required to execute the usual contract bond; in default of which, his tender will be considered cancelled, and his earnest money will be forfeited.

7. The name of the successful competitor, whose tender has been accepted, will be posted on the Notice Board in the Executive Engineer's Office in due course. No enquiry regarding the acceptance or rejection of a tender will receive any reply.

8. On acceptance of one of the tenders, the earnest money on rejected tenders will be returned.

9. Rates once tendered will not be enhanced on any account.

10. Rates for non-tendered and non-estimated items shall be as per schedule rates of the Department or those fixed by the Executive Engineer after working out data with not more than 10 per cent for Contractor's profit.

11. In all matters not specifically provided for and in all matters of dispute about rates, quantities, measurements, quality of works, etc., and in all disputes of any kind, the decision of the Executive Engineer will be final and legally binding.

12. Quotations must be given in words as well as in figures and they must be in specific term of unit shown against each item of work. Any quotation quoted at so much percentage less or more than estimated rate will not be accepted.

Abstract estimate for constructing a Gopuram over Sree Dharmarayaswamy Temple at Ulsoorpet, Bangalore City.

Sl. No.	Items of work	Per	Quantity	Estimated rate	Rates to be quoted in	
					Words	Figures
	III. Floor between 28½′ to 34′ above ground level.			Rs. a. p.		
1	Burnt brick in mortar for superstructure including scaffolding at 34′ ..	C.ft.	535	0 6 6		
2	Burnt brick in mortar arch work front and rear	„	38	0 7 6		
3	Burnt stone slabs 6″ thick roughly dressed including hoisting and fixing in mortar	„	4	0 6 6		
4	Supplying and fixing R.S. Girders including bolts, fish plates, hoisting and fixing, etc., complete with painting 9″×4″	Cwt.	7.3	11 0 0		
5	Boxing girders with brick in mortar including plastering, etc., complete ..	R.ft.	35	0 8 0		
6	Chunam plastering with smooth hand ground mortar finish	Sqr.	3.07	4 0 0		
7	Constructing ornamental cornice with brick in mortar finished with smooth lime plaster as per drawing—					
	(*a*) Cyma recta type of cornice 1′ high at the bottom	R.ft.	64	2 0 0		
	(*b*) Cyma recta inverted type at top 8″ high	„	56	1 8 0		
	(*c*) Flat cornice fillet type 9″ ..	„	52	1 0 0		
8	Constructing the mantapam moulding with brick in mortar with smooth lime motar including top Vimanam Kalasas, etc., as per drawing about 3¼′×¾′ at front and rear ..	Each	2	40 0 0		
9	White and colour washing, etc. ..	Sqr.	12	0 6 0		
	IV. Floor between 34′ and 39½′ above G. L.					
1	Burnt brick in mortar including scaffolding	C.ft.	347	0 6 6		
2	Burnt brick in mortar Arch work front and rear	„	21	0 7 6		

Sl. No.	Items of work	Per	Quantity	Estimated rate	Rates to be quoted in	
					Words	Figures
				Rs. a. p.		
3	Burnt stone slabs 6″ thick roughly dressed including hoisting and fixing	S.ft.	9	0 6 6		
4	Supplying and fixing R. S. Girders including hoisting and fixing with bolts, fish plates, etc., and one coat of red oxide paint 8″×4″ ..	Cwt.	5.6	11 0 0		
5	Boxing girders with wiring and plastering, etc., complete	R.ft.	30½	0 8 0		
6	Chunam plastering with smooth hand grounding mortar finish ..	Sqr.	2.74	4 0 0		
7	Constructing cornice with burnt brick in mortar as per III Floor—					
	(*a*) Base cornice 9″ high	R.ft.	55	1 8 0		
	(*b*) Top „ 6″ „	„	47	1 4 0		
	(*c*) Intermediate fillet 8″	„	43	1 0 0		
8	Mantapam moulding as per III Floor about 3′×4′ at the front and rear	Each	2	30 0 0		
9	White and colour washing	Sqr.	10	0 6 6		
	Topmost dome between 39½′ and 46′ above G. L.					
1	Burnt brick in mortar including scaffolding	C.ft.	146	0 7 0		
2	Burnt brick in mortar Arch work for dome portion	„	173	0 8 6		
3	Wire cut brick in cement mortar ..	„	21	1 0 0		
4	Chunam plastering with smooth hand grounding 3 coats	Sqr.	1.65	5 0 0		
5	Highly ornamental work with smooth lime plaster all over the outside as per drawing	S.ft.	213	2 0 0		
6	Constructing cornice as per III and IV Floor—					
	(*a*) Base cornice Cyma recta type 9″ high	R.ft.	46	1 10 0		
	(*b*) Do at top 6″ high	„	40	1 8 0		
7	Constructing sarabha moulding (3′×3½′) as per drawing with smooth lime plaster finish	Each	4	50 0 0		
8	White and colour washing	Sqr.	16	0 8 0		
	Improvements to the existing 1st and 2nd and Ground Floors.					
1	Finishing the cornice as per drawing with smooth plaster finish ..	R.ft.	162	1 0 0		
2	Flooring with burnt stone slabs 4″ thick 2 line dressed at top fixed over sand bed and cement pointing etc., complete	Sqr.	12.04	40 0 0		
3	Cement pointing to the joints of slabs of wall on the outside ground floor	„	9.94	3 0 0		
4	Chunam plastering inside	„	13.17	3 4 0		
5	Supplying and fixing R. S. Girders with bolts, fish plates, painting etc., etc.	Cwt.	16.5	11 0 0		
6	Burnt stone slabs roughly dressed and fixed in mortar bed slabs of girders	S.ft.	12	0 6 0		
7	Boxing girders with wiring and plastering etc., complete	R.ft.	57½	0 8 0		

N. KRISHNIENGAR,
Executive Engineer.